



DRIVE-BY-WIRE BF200

- Honda's exclusive BLAST™ system improves acceleration at low speeds
- One of the quietest outboards in its class
- Lean Burn Control
- Multi-port Programmed Fuel Injection

HONDA MARINE

ENGINE

Type	4-Stroke, SOHC, 60° V6, 24 Valves	Displacement	3,583 cc / 219 cubic in.
Bore & Stroke	89 mm x 96 mm (3.50 x 3.78 in.)	Full Throttle RPM Range	5,000-6,000 RPM
Propshaft Rated Horsepower (HP)	200 hp @ 5,500 RPM	Cooling System	Water Cooled
Fuel Delivery	Programmed Electronic Fuel Injection (PGM-FI)	Recommended Fuel	Unleaded Gas. (Min. Pump Octane 86)
Tank Capacity	N/A	Ignition System	Microcomputer Programmed
Starting System	Electric	Exhaust	Through Prop Hub
Lubrication	Pressure Lubrication (Trochoid pump)	Recommended Oil	Honda 10W30 FC-W™ outboard motor oil
Oil Capacity	7.80 L (8.24 US qt) with oil filter repl.	Trim Range	-4° to +16°
Tilt Range	68°	Steering Angle	30°

DRIVE

Gear Ratio	2 : 1	Gear Shift	F-N-R
------------	-------	------------	-------

EQUIPMENT

Alternator (Manual Start)	N/A	Alternator (Electric Start)	90 amp
Battery Charging Power	60 amp and AMP+	Power Tilt	N/A
Power Trim & Tilt	Standard	Gas Assisted Tilt	N/A
Oil Pressure Alert	Standard	Over Rev-Limiter	Standard
Temperature Alert	Standard	Water in Fuel Alert	Standard
Battery Condition Alert	N/A	Speedometer Pickup	N/A
Variable Speed Trolling Kit	N/A	Rudder Meter Kit	N/A
Tilt Limiter Kit	N/A	Trolling Mode Range	N/A
Cruise Control Range	N/A		

DIMENSIONS

Overall Width	660 mm / 26 in.	Transom Height (X Type)	635 mm / 25 in.
Transom Height (U Type)	762 mm / 30 in.		

PROPELLER

Propeller Type (Material)	Optional	Propeller Diameter x Pitch (S-Type)	N/A
Propeller Diameter x Pitch (L-Type)	N/A	Propeller Diameter x Pitch (BF(P))	N/A

DRY WEIGHT			
SH type	N/A	SCHC-Type	N/A
SHGC-Type	N/A	SHS-Type	N/A
SRC-Type	N/A	LH type	N/A
LCHC-Type	N/A	LHTC-Type	N/A
LHGC-Type	N/A	LRTC-Type	N/A
L-Type	276 kg / 609 lb.	X-Type	286 kg / 631 lb.
XC-Type	N/A	XRTC-Type	N/A
XX-Type	N/A	U-Type	291 kg / 642 lb. With propeller mounted
UC-Type	N/A		

Models and/or colours may not be exactly as shown. Errors and omissions excepted. Specifications are subject to change without notice. See your Honda Marine dealer for details.

For optimum performance and safety, please read your owner's manus before operating your Honda product. Always wear the appropriate safety gear when operating your Honda.

®/TM — Trademarks of Honda Canada Inc. or used under licence from Honda Motor Co., Ltd. or third parties.