



DRIVE-BY-WIRE

BF350

- BLAST™ (Boosted Low Speed Torque)
- VTEC® Technology
- Lean burn control®
- Power generation capacity of maximum 70A with AMP+
- Honda's exclusive iST® (Intelligent Shift and Throttle®)



ENGINE			
Type	4-Stroke, SOHC, 60° V8, 32 Valve	Displacement	4,952 cc / 302 cubic in
Bore & Stroke	89 mm x 99.5 mm (3.50 x 3.92 in)	Full Throttle RPM Range	350 hp @ 6,000 RPM
Propshaft Rated Horsepower (HP)	5,000 - 6,000 RPM	Cooling System	Water Cooled
Fuel Delivery	Programmed Fuel Injection	Recommended Fuel	Unleaded Gas. (Min. Pump Octane 86)
Tank Capacity	N/A	Ignition System	Microcomputer Programmed
Starting System	Electric	Exhaust	Through Prop Hub
Lubrication	Wet Sump	Recommended Oil	Honda 10W30 FC-W™ outboard motor oil
Oil Capacity	10.20 L (10.8 US qt) without oil filter replacement;10.40 L (11 US qt) with oil filter replacement	Trim Range	-4° to +15°
Tilt Range	68°	Steering Angle	30°
DRIVE			
Gear Ratio	1.79:1	Gear Shift	F-N-R
EQUIPMENT			
Alternator (Manual Start)	N/A	Alternator (Electric Start)	93 Amps
Battery Charging Power	70 Amps	Power Tilt	N/A
Power Trim & Tilt	Standard	Gas Assisted Tilt	N/A
Oil Pressure Alert	Standard	Over Rev-Limiter	Standard
Temperature Alert	Standard	Water in Fuel Alert	Standard
Battery Condition Alert	Standard	Speedometer Pickup	Standard
Variable Speed Trolling Kit	Optional	Rudder Meter Kit	N/A
Tilt Limiter Kit	Standard	Trolling Mode Range	650-1000 RPM
Cruise Control Range	650-6000 RPM in 50 RPM Increments		
DIMENSIONS			
Overall Width	650 mm / 25.6 in.	Transom Height (X Type)	638 mm / 25 in.
Transom Height (U Type)	765 mm / 30 in.		
PROPELLER			
Propeller Type (Material)	Optional	Propeller Diameter x Pitch (S-Type)	N/A
Propeller Diameter x Pitch (L-Type)	N/A	Propeller Diameter x Pitch (BF(P)	N/A

DRY WEIGHT			
SH type	N/A	SCHC-Type	N/A
SHGC-Type	N/A	SHS-Type	N/A
SRC-Type	N/A	LH type	N/A
LCHC-Type	N/A	LHTC-Type	N/A
LHGC-Type	N/A	LRTC-Type	N/A
L-Type	N/A	X-Type	347 kg / 765 lb.
XC-Type	N/A	XRTC-Type	N/A
XX-Type	N/A	U-Type	352 kg / 776 lb.
UC-Type	N/A		

Models and/or colours may not be exactly as shown. Errors and omissions excepted. Specifications are subject to change without notice. See your Honda Marine dealer for details.
For optimum performance and safety, please read your owner's manus before operating your Honda product. Always wear the appropriate safety gear when operating your Honda.
®/TM — Trademarks of Honda Canada Inc. or used under licence from Honda Motor Co., Ltd. or third parties.