



DRIVE-BY-WIRE BF115C

- BLAST™ (Boosted Low Speed Torque)
- Lean Burn Control®
- Meets NMEA 2000 standards
- Largest displacement in its class
- Optional variable speed trolling

HONDA

MARINE

ENGINE

Type	4-Stroke DOHC 4 Cylinder / 16 Valves	Displacement	2,354 cc / 144 cubic in.
Bore & Stroke	87 x 99 mm (3.43 x 3.89 in.)	Full Throttle RPM Range	4,500-6,000 RPM
Propshaft Rated Horsepower (HP)	115 hp @ 5,250 RPM	Cooling System	Water Cooled
Fuel Delivery	Programmed Electronic Fuel Injection (PGM-FI)	Recommended Fuel	Unleaded Gas. (Min. Pump Octane 86)
Tank Capacity	N/A	Ignition System	Microcomputer Programmed
Starting System	Electric	Exhaust	Through Prop Hub
Lubrication	Wet Sump	Recommended Oil	Honda 10W30 FC-W™ outboard motor oil
Oil Capacity	6.70 L (7.08 US qt) with oil filter repl.	Trim Range	-4° to +16°
Tilt Range	68°	Steering Angle	30°

DRIVE

Gear Ratio	2.14 : 1	Gear Shift	F-N-R
------------	----------	------------	-------

EQUIPMENT

Alternator (Manual Start)	N/A	Alternator (Electric Start)	55 amp
Battery Charging Power	40 amp	Power Tilt	N/A
Power Trim & Tilt	Standard	Gas Assisted Tilt	N/A
Oil Pressure Alert	Standard	Over Rev-Limiter	Standard
Temperature Alert	Standard	Water in Fuel Alert	Standard
Battery Condition Alert	Standard	Speedometer Pickup	Standard
Variable Speed Trolling Kit	Optional	Rudder Meter Kit	N/A
Tilt Limiter Kit	Standard	Trolling Mode Range	N/A
Cruise Control Range	N/A		

DIMENSIONS

Overall Width	610 mm / 24 in.	Transom Height (L-Type)	508 mm / 20 in.
Transom Height (X-Type)	635 mm / 25 in.		

PROPELLER

Propeller Type (Material)	Optional	Propeller Diameter x Pitch (S-Type)	N/A
Propeller Diameter x Pitch (L-Type)	N/A	Propeller Diameter x Pitch (BF(P))	N/A

DRY WEIGHT			
SH type	N/A	SCHC-Type	N/A
SHGC-Type	N/A	SHS-Type	N/A
SRC-Type	N/A	LH type	221 kg / 487 lb.
LCHC-Type	N/A	LHTC-Type	N/A
LHGC-Type	N/A	LRTC-Type	N/A
L-Type	N/A	X-Type	224 kg / 493 lb.
XC-Type	N/A	XRTC-Type	N/A
XX-Type	N/A	U-Type	N/A
UC-Type	N/A		

Models and/or colours may not be exactly as shown. Errors and omissions excepted. Specifications are subject to change without notice. See your Honda Marine dealer for details.
For optimum performance and safety, please read your owner's manual before operating your Honda product. Always wear the appropriate safety gear when operating your Honda.
®/TM — Trademarks of Honda Canada Inc. or used under licence from Honda Motor Co., Ltd. or third parties.