



MID-RANGE BF60

- BLAST™ (Boosted Low Speed Torque)
- Lean burn control®
- Meet NMEA 2000 Standards
- Best-in-class fuel efficiency
- Optional Variable Speed Trolling

HONDA

MARINE

ENGINE

Type	4-Stroke SOHC 3 Cylinder / 12 Valves	Displacement	998 cc / 61.0 cubic in.
Bore & Stroke	73 mm x 79.5 mm (2.9 x 3.1 in.)	Full Throttle RPM Range	5,000-6,000 RPM
Propshaft Rated Horsepower (HP)	60 hp @ 5,500 RPM	Cooling System	Water Cooled
Fuel Delivery	Programmed Electronic Fuel Injection (PGM-FI)	Recommended Fuel	Unleaded Gas. (Min. Pump Octane 86)
Tank Capacity	N/A	Ignition System	Microcomputer Programmed
Starting System	Electric	Exhaust	Through Prop Hub
Lubrication	Pressure Lubrication (Trochoid pump)	Recommended Oil	Honda 10W30 FC-W™ outboard motor oil or SAE 10W30 API service classification SJ or later
Oil Capacity	2.70 L (2.85 US qt) with oil filter repl.	Trim Range	-4° to +16°
Tilt Range	60°	Steering Angle	30° remote , 50° tiller (with tiller model LHTC)

DRIVE

Gear Ratio	2.07 : 1	Gear Shift	F-N-R
------------	----------	------------	-------

EQUIPMENT

Alternator (Manual Start)	N/A	Alternator (Electric Start)	27 amp
Battery Charging Power	22 amp	Power Tilt	N/A
Power Trim & Tilt	Standard	Gas Assisted Tilt	N/A
Oil Pressure Alert	Standard	Over Rev-Limiter	Standard
Temperature Alert	Standard	Water in Fuel Alert	N/A
Battery Condition Alert	Standard	Speedometer Pickup	Standard
Variable Speed Trolling Kit	Optional	Rudder Meter Kit	Optional
Tilt Limiter Kit	Optional	Trolling Mode Range	N/A
Cruise Control Range	N/A		

DIMENSIONS

Overall Width	417 mm / 16.4 in.	Transom Height (L-Type)	521 mm / 20.5 in.
---------------	-------------------	-------------------------	-------------------

PROPELLER

Propeller Type (Material)	Optional	Propeller Diameter x Pitch (S-Type)	N/A
Propeller Diameter x Pitch (L-Type)	N/A	Propeller Diameter x Pitch (BF(P))	N/A

DRY WEIGHT			
SH type	N/A	SCHC-Type	N/A
SHGC-Type	N/A	SHS-Type	N/A
SRC-Type	N/A	LH type	N/A
LCHC-Type	N/A	LHTC-Type	115 kg / 254 lb. (With propeller mounted)
LHGC-Type	N/A	LRTC-Type	110 kg / 243 lbs. (With propeller mounted)
L-Type	N/A	X-Type	N/A
XC-Type	N/A	XRTC-Type	N/A
XX-Type	N/A	U-Type	N/A
UC-Type	N/A		

Models and/or colours may not be exactly as shown. Errors and omissions excepted. Specifications are subject to change without notice. See your Honda Marine dealer for details.

For optimum performance and safety, please read your owner's manus before operating your Honda product. Always wear the appropriate safety gear when operating your Honda.

®/TM — Trademarks of Honda Canada Inc. or used under licence from Honda Motor Co., Ltd. or third parties.