



PORTABLES BF20

- Easy starting
- Lightest in class
- High output charging
- 4-Front Corrosion Protection
- Large displacement for exceptional power

HONDA

MARINE

ENGINE

Type	4-Stroke SOHC 2 Cylinders / 4 Valves	Displacement	350 cc / 21.4 cubic in.
Bore & Stroke	59 mm x 64 mm (2.32 x 2.52 in.)	Full Throttle RPM Range	5,000-6,000 RPM
Propshaft Rated Horsepower (HP)	20 hp @ 5,500 RPM	Cooling System	Water Cooled
Fuel Delivery	1 Carburetor	Recommended Fuel	Unleaded Gas. (Min. Pump Octane 86)
Tank Capacity	N/A	Ignition System	CDI
Starting System	Electric and Recoil	Exhaust	Under Water, above propeller
Lubrication	Forced Lubrication (Trochoid pump)	Recommended Oil	SAE 10W30 API service classification SJ or later
Oil Capacity	1.30 L (1.37 US qt) with oil filter repl.	Trim Range	4-Stage 8°-12°-16°-20° (LHG-Type)
Tilt Range	71° (S-type) 72° (L-Type)	Steering Angle	45° right and left

DRIVE

Gear Ratio	2.08 : 1	Gear Shift	F-N-R
------------	----------	------------	-------

EQUIPMENT

Alternator (Manual Start)	6 amp / 76 watts	Alternator (Electric Start)	12 amp / 152 watts
Battery Charging Power	N/A	Power Tilt	LRTC model only
Power Trim & Tilt	N/A	Gas Assisted Tilt	LHGC model only
Oil Pressure Alert	Standard	Over Rev-Limiter	Standard
Temperature Alert	Standard	Water in Fuel Alert	N/A
Battery Condition Alert	N/A	Speedometer Pickup	N/A
Variable Speed Trolling Kit	N/A	Rudder Meter Kit	N/A
Tilt Limiter Kit	N/A	Trolling Mode Range	N/A
Cruise Control Range	N/A		

DIMENSIONS

Overall Width	350 mm / 13.7 in.	Transom Height (S-Type)	432 mm / 17 in.
Transom Height (L-Type)	563 mm / 22.2 in.		

PROPELLER

Propeller Type (Material)	4-Blade (Aluminum)	Propeller Diameter x Pitch (S-Type)	235 mm x 254 mm / 9-1/4 x 10 in.
Propeller Diameter x Pitch (L-Type)	235 mm x 254 mm / 9-1/4 x 10 in.	Propeller Diameter x Pitch (BF(P))	N/A

DRY WEIGHT			
SH type	46.5 kg / 103 lbs.	SCHC-Type	N/A
SHGC-Type	N/A	SHS-Type	50 kg / 110 lbs.
SRC-Type	50.5 kg / 111 lbs.	LH type	49.5 kg / 109 lbs.
LCHC-Type	N/A	LHTC-Type	N/A
LHGC-Type	58.5 kg / 129 lbs.	LRTC-Type	50.0 kg / 110 lbs.
L-Type	N/A	X-Type	N/A
XC-Type	N/A	XRTC-Type	N/A
XX-Type	N/A	U-Type	N/A
UC-Type	N/A		

Models and/or colours may not be exactly as shown. Errors and omissions excepted. Specifications are subject to change without notice. See your Honda Marine dealer for details.

For optimum performance and safety, please read your owner's manus before operating your Honda product. Always wear the appropriate safety gear when operating your Honda.

®/TM — Trademarks of Honda Canada Inc. or used under licence from Honda Motor Co., Ltd. or third parties.